

RFID ČITAČI

PART No: PACD-102

NIŽE, U ORIGINALU

Model No.: PCD-102 EM, MF

Introduction:

PCD-102E: 125KHz Proximity card reader
PCD-102M: 13.56MHz Mifare card reader

Features:

- > 125KHz Proximity /13.56MHz Mifare Card Reader
- > Read Range: Up to 10cm (125KHz) / 5cm (13.56MHz)
- > 26/34bit Wiegand (default)
- > Easy to install on Metal Door Frame or Mullion
- > External LED Control
- > External Buzzer Control
- > Indoor / Outdoor Operation
- > Solid Epoxy Potted
- > Waterproof IP65
- > Reverse Polarity Protection



Model	PACD-102EM and PACD-102MF
Read Range	PACD-102EM: Up to 10cm, PACD-102MF:Up to 5cm
Reading Time (Card)	≤300ms
Power / Current	DC 6-14V / Max.70mA
Input Port	2ea (External LED Control, External Buzzer Control)
Output Format	26bit/34bit Wiegand (default)
LED Indicator	2 Color LED Indicators(Red and Green)
Beeper	Yes
Operating Temperature	-20° to +65°C
Operating Humidity	10% to 90% relative humidity non-condensing
Colour	Black
Material	ABS+PC with texture
Dimension(W x H x T)mm	124 x 76x 23.5mm
Weight	50g
Index of Protection	IP65



+381 11 355 7599
+381 63 598 017
office@aspekt.rs