

RFID Čitač & Šifратор

VODO-OTPORAN, SAMOSTALAN I SA WIEGAND KOMUNIKACIJOM

Waterproof metal Standalone Access Controller, for single door entrance, with card reader and keyboard input in one function, Support Wiegand output & input, can be used as a card reader control



Product Parameter	Parameter Description
Power Supply:	12VDC + 10%
Access control Interface	WG26/34 interface
Size:	130x69x18mm
Wiegand:	WG26/34 input and output port
User capacity	8000
Card type	EM ID card
Relative humidity:	10%-90% RH
Password	4 digit PIN code
Compatible Cards	125KHz EM/13.56mhz standard card
Card Reading Distance	1.18~2.36in
Color	Silver/Red bronze/Green Bronze/Golden
opening method	CARD, PIN, CARD+PIN
Weight:	0.5KG
Package:	115x70x22mm

ADVANTAGE

1. completely independent access control, directly through the keyboard to achieve password, card management and other functions. 2.supports Wiegand 26 output&input, can be used as a card reader. 3.support card, password, card with password three seed certification management. 4.reader sensor with high sensitivity, less than 0.1 seconds. 5.supports a password to open the door, stand-alone card capacity up to 8000. 6.high-quality stainless steel materials, with tamper alarm and door sensor alarm functions. 7.exit button and doorbell input function.