

14-Apr-2004



RFID Čitač sa tastaturom

SAMOSTALAN I „WIEGAND“ PLATFORMA

METALNO KUĆIŠTE "NO WATER PROOF"

Model: ACAM208-EM-NW – EM (125KHz)


Model: ACAM208-M1-NW – M1 (13.56MHz)

- Waterproof case
- Strong Zinc Alloy Electroplated case
- Full programming from the keypad
- 2000 uses, supports Card, PIN, Card + PIN
- Card Type: EM (125KHz), M1 (13.56MHz)
- Card Reading Distance: 3-6 cm
- Stand alone and wiegand 26 output
- Backlight keys
- Adjustable:
 - o Door Output time,
 - o Alarm time,
 - o Door Open time
 - o Alarm Time: 0~3 minutes
- Very low power consumption (30mA)
- Active Current: < 60mA
- Idle Current: 25±5 mA
- Fast operating speed, < 20ms with 2000 users
- Lock output current short circuit protection
- Easy to install and program
- Tamper & buzzer
- LED (Red, Yellow and Green) the working status
- Operating Voltage: 9-28V DC
- Lock Output Load: Max 20A
- Adjustable Door Relay time: 0 - 99 seconds
- Alarm Output Load: Max 20A
- Operating Temperature: -20°C ~ 55°C
- Operating Humidity: 10%- 90% RH
- Dimensions: 120*56*20mm
- Weight: 0.46kg
- Wiring Connections:
 - o Electric Lock
 - o Exit Button
 - o External Alarm
- User programming manual (<http://www.aspektdoo.com/SRBDownload.html>)
- Installation manual (<http://www.aspektdoo.com/SRBDownload.html>)

RFID & TASTATURA
metalno kućište, ne vodo-otporno
125KHz, ili
13.56MHz



Distributer:



ASPEKT System Integration d.o.o.
Požeška br. 67a, 11000 Belgrade, Serbia
Phone: +381 11 3557 599
Mobile: +381 63 598 033
office@aspekt.rs