

14-Apr-2004



# RFID Čitač sa tastaturom

SAMOSTALAN I „WIEGAND“ PLATFORMA

## METALNO KUĆIŠTE (IP68) ANTI-VANDAL

Model: AS600E – EM (125KHz)


Model: AS600E – M1 (13.56MHz)

- Waterproof, conforms to IP68
- Strong Zinc Alloy Electroplated case
- Anti-vandal case
- Full programming from the keypad
- 2000 uses, supports Card, PIN, Card + PIN
- Option 8000 users
- Card Type: EM (125KHz), M1 (13.56MHz)
- Card Reading Distance: 3-6 cm
- Stand alone and wiegand 26 output
- Backlight keys
- Adjustable:
  - Door Output time,
  - Alarm time,
  - Door Open time
  - Alarm Time: 0~3 minutes
- Very low power consumption (30mA)
- Active Current: < 60mA
- Idle Current: 25±5 mA
- Fast operating speed, < 20ms with 2000 users
- Lock output current short circuit protection
- Easy to install and program
- Tamper & buzzer
- LED (Red, Yellow and Green) the working status
- Operating Voltage: 9-28V DC
- Lock Output Load: Max 20A
- Adjustable Door Relay time: 0 -99 seconds
- Alarm Output Load: Max 20A
- Operating Temperature: **-45°C ~ 60°C**
- Operating Humidity: 10%- 90% RH
- Dimensions: 120\*56\*20mm
- Weight: 0.46kg
- Wiring Connections:
  - Electric Lock
  - Exit Button
  - External Alarm
- User programming manual ( <http://www.aspektdoo.com/SRBDownload.html> )
- Installation manual ( <http://www.aspektdoo.com/SRBDownload.html> )

**RFID & TASTATURA**  
metalno kućište (IP68); anti vandal  
125KHz, ili  
13.56MHz



Distributer:



ASPEKT System Integration d.o.o.  
Požeška br. 67a, 11000 Belgrade, Serbia  
Phone: +381 11 3557 599  
Mobile: +381 63 598 033  
office@aspekt.rs