

14-Apr-18



Pistol

Charging cradle

External Antenna





1D Barcode



2D Barcode



RFID



NFC



Fingerprint



InfraRed



3G



WiFi



Bluetooth



GPS



Camera

Physical Characteristics

Dimensions	176mm x 76mm x 28.5mm / 6.93 x 2.99 x 1.12in
Weight	292g/ 10.30oz
Display	4" WVGA (480*800), 16.7M colors
Touch Panel	Rugged capacitive touch panel
Power	Main battery: Li-ion, 3200mAh Pistol battery: Li-ion, 5200mAh (Optional)
Expansion Slot	1 PSAM, 1 SIM, 1 MicroSD (TF) slot
Interfaces	USB Micro-B
Audio	0.5W speaker, build-in microphone
Keypad	Numeric / Qwerty
Sensors	Light Sensor, Proximity Sensor

Performance

CPU	Cortex-A7 1.3GHz quad-core
RAM	1GB
ROM	4GB
Expansion	Supports up to 32GB Micro SD card

Developing Environment

Operating System	Android 4.4.2
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating Temp.	14°F to 122°F / -10°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5%RH - 95%RH non condensing
Drop Specification	Multiple 1.2m drops to concrete across the operating temperature range
Tumble Specification	1000 x 0.5m/ 1.64ft falls at room temperature
Sealing	IP64

Communication

WLAN	IEEE802.11 b/g/n
WWAN	GSM/GPRS/EDGE Quad Band (850/900/1800/1900MHz) WCDMA (850/1900/2100MHz)
Bluetooth	Bluetooth 4.0
GPS	GPS, AGPS

Biometric (Optional)

Functions	Enrollment, compare, deletion etc.
Sensor	TCS25S
Sensor Type	Capacitive Sensor
Resolution	508DPI
Memory	1,000 PCS fingerprints

InfraRed (Optional)

Wavelength	940nm
Frequency	38kHz
Range	> 4m

Barcode Scanning (Optional)

1D Linear Scanner	
1D Laser / CCD	Symbol SE965
Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Imager Scanner	
2D CMOS Laser Scanner	Symbol SE4750
Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

RFID (Optional)

LF	
Frequency	125kHz, 134kHz (FDX-B / HDX)
Protocol	ISO11784/5, ISO18000-2
Chips	R/O ID card, eg EM4100/4200, TK4100 R/W ID card, eg EM4305/HITAG S Animal tags Others for customization
Range	3-8cm
LF (with external antenna)	
Frequency	134kHz (FDX-B+HDX)
Protocol	ISO11784/5
Chips	Animal tags Others for customization
Range	3-12cm, external antenna 3-20cm, with a 75cm extension antenna
HF	
Frequency	13.56MHz
Protocol	ISO14443A/B, ISO15693
Chips	M1 card (S50/S70), M0 (Ultralight), M3 (Desfire D40/D41/D81), CPU_A card CPU_B card ICODE II, TI2048, LRI64K Others for customization
Range	3-8cm
NFC	
Frequency	13.56MHz
Protocol	ISO/IEC 18092 (ECMA 340) ISO/IEC 21481 (ECMA 352)
Range	2-4cm

* For the UHF specifications, please check C4050 UHF specification sheet

Other Modules (Optional)

Camera	8MP autofocus camera with flash
PSAM	ISO7816 Protocol, 1 PSAM slot

Accessories



AC Adapter



Snap-on



USB cable



Cradle (Optional)




Pistol (Optional)



Fingerprint Snap-on (Optional)

Distributer:



ASPEKT System Integration d.o.o.
Požeška br. 67a, 11000 Belgrade, Serbia
Phone: +381 11 3557 599
Mobile: +381 63 598 033
office@aspekt.rs