

14-Apr-17



## POS PRINTER

### AMS-80III

#### Features:

- Easy loading
- water proof; dust proof; oil-drop proof design
- GB18030 font set
- multiple language printing
- printer status remote monitor
- full/partial cutting by optional
- error warning supporting
- Linux system driver supporting
- blackmark detection supporting
- compatible with both EPSON ESC/POS and Star command
- 256K Bytes NV Logo download and printing supporting



Printing method	Thermal dot line printing
Printing width	80 mm
Dot/line	576 dots/line
Printing speed	180 mm/s
Interface	Parallel/RS-232/USB/RS-232+USB/Ethernet
Paper width	79.5±0.5mm×φ83 mm
Line pitch	3.75 mm (adjustable by command)
Column numbers	Font A – 42/48 ;Font B - 56/64; simple/complex Chinese- 21/24
Font size	ANK Font A : 1.5×3.0mm (12×24 dots) ANK Font B : 1.1×2.1mm (9×17 dots) simple/complex Chinese : 3.0×3.0mm (24×24 dots)
Character table	PC347 (Standard Europe) 、 Katakana、 PC850 (Multilingual) 、 PC860 (Portuguese) 、 PC863 (Canadian-French) 、 PC865 (Nordic) 、 West Europe、 Greek、 Hebrew、 East Europe、 Iran、 WPC1252、 PC866 (Cyrillic#2) 、 PC852 (Latin2) 、 PC858、 IranII、 Latvian、 Arab ic、 PT151 (1251)
Barcode type	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128
Cutter	Full/partial by optional
buffer	64k bytes
NV Flash	128k bytes
Cash box input	DC 24V/1A
Input	AC 110V/220V, 50~60Hz
Adaptor	output : DC 24V/2.5A
Weight	1.56 kg
Dimension	200×145×137mm (L×W×H)
Working	temperature: 0~45°C, humidity: 10~80%
Storage	temperature: -10~60°C, humidity: 10~90%
Reliability	100 KM