

**UHF OPREMA - RFID ČITAČI DALEKOG DOMETA (0.18m ~ 30m) I OSTALO**

Frekvencija dozvoljena za "public" upotrebu u EU 868Mhz

Opcija: Frekvencija dozvoljena za "public" upotrebu u US 968 MHz

Opcije komunikacije Wiegand / RS232/RS485 i USB

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	1 AZT-RY-105 AZT   UHF RFID Desktop Reader/writer   USB   effective distance up to 18cm - 105mm×70mm×11mm   0.3kg; 902~928MHz, 865~868MHz - Support protocols: UHF EPC Gen2 (ISO18000-6C), ISO18000-6B   DLL & DEMO - Provide DLL and Demonstration Software Source code to facilitate further development	kom	245.00
	21 AZT-RY-402 AZT   UHF Citac   bez antene   RS232, wiegand 26/34   170 × 120 × 50 mm - 902~928MHz, 865~868MHz   -25°C~+95°C; 0.4kg   DC 7.5V~12V, 3A - Support protocols: ISO18000-6B, EPC Class 1, EPC Class 1 GEN 2   SDK - RF power range: 0~30 dBm   Identify tag mode: trigger, or auto	kom	245.00
	41 AZT-STU-A5 AZT   UHF Antena   Gain: 5dBi   polarizacija - Rang "čitanja" očekivan 0.7 ~ 3m, direktno zavisi od okruženja u koje se postavlja	kom	115.00
	42 AZT-STU-A7 AZT   UHF Antena   Gain: 7dBi   omni-direkciona - Rang "čitanja" očekivan 0.7 ~ 3m, direktno zavisi od okruženja u koje se postavlja	kom	120.00
	43 AZT-STU-A8 AZT   UHF Antena   Gain: 8dBi   polarizacija E68°; H65°   2.3kg   280×280×40mm - EU slobodna za koriscenje frekvencija; protocol: ISO-18000-6B/6C - Rang "čitanja" očekivan 3 ~ 6m, direktno zavisi od okruženja u koje se postavlja	kom	145.00
	44 AZT-STU-A12(12dBi) AZT   UHF Antena   Gain: 12dBi   polarizacija E38°; H40°   4.5kg   445×445×40mm - EU slobodna za koriscenje frekvencija; protocol: ISO-18000-6B/6C - Rang "čitanja" očekivan 6 ~ 12m, direktno zavisi od okruženja u koje se postavlja	kom	195.00

**UHF OPREMA - RFID ČITAČI DALEKOG DOMETA (0.18m ~ 30m) I OSTALO**

Frekvencija dozvoljena za "public" upotrebu u EU 868Mhz

Opcija: Frekvencija dozvoljena za "public" upotrebu u US 968 MHz

Opcije komunikacije Wiegand / RS232/RS485 i USB




FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	45 AZT-STU-A15(15dBi) AZT   UHF Antena   Gain: 15dBi   polarizacija 16°; H65°   9.5kg   1200*280*90 mm - EU slobodna za koriscenje frekvencija; protocol: ISO-18000-6B/6C - Rang "čitanja" očekivan 12 ~ 30m, direktno zavisi od okruženja u koje se postavlja	kom	295.00
	71 ACAM-812A GB - UHF RFID Čitač   Long range: 2 ~ 6m   weigand 26, RS232/485	kom	145.00
	72 ACAM-802A GB - UHF RFID Čitač   Long range: 6 ~ 12m   weigand 26, RS232/485	kom	195.00
	73 ACAM-801A GB - UHF RFID Čitač   Long range: 10 ~ 20m   weigand 26, RS232/485	kom	225.00
	75 ACAM-811A GB - UHF RFID Čitač   Muti-tag Long range: 3 ~ 8m   weigand 26, RS232/485	kom	175.00
	76 ACAM-819A GB - UHF RFID Čitač   Muti-tag Long range: 10 ~ 20m   weigand 26, RS232/485	kom	245.00

**UHF OPREMA - RFID ČITAČI DALEKOG DOMETA (0.18m ~ 30m) I OSTALO**

Frekvencija dozvoljena za "public" upotrebu u EU 868Mhz

Opcija: Frekvencija dozvoljena za "public" upotrebu u US 968 MHz

Opcije komunikacije Wiegand / RS232/RS485 i USB

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>81 UHF-ID-Zebra</p> <p>UHF ID Kartica   brand name Zebra   ISO CR 80   0.76mm   high glossy                      - EPCglobal UHF Class 1 Gen 2 (ISO 18000-6C)   Global 860-960 MHz                      - Tehnologija stampe: na ID Crad Printerima                      - Rang citanja: 3 ~ 12m, zavisi od odabrane antene i okruzenja</p>	kom	3.50
	<p>82 UHF2</p> <p>AZT   UHF nalepnice   40x40mm   Bela   za T/T Bar-code štampu   u rolni                      - Standardi: ISO CR80; ISO-18000-6C   -20C~ +80C                      - Bela, blanko i za štampu bar-code, logo, itd                      - Rang citanja: 5 ~ 8m, zavisi od odabrane antene i okruzenja</p>	kom	1.45
	<p>83 AUHF-ZT-JXX-U8654</p> <p>AZT   UHF nalepnice   86*54mm   Cip H3; Antena 70*17mm   Rang citanja: 5 ~ 10m                        - Standardi: ISO CR80; ISO-18000-6C   -20C~ +80C                      - Bela, blanko i za štampu bar-code, logo, itd                      - Rang citanja: 5 ~ 12m, zavisi od odabrane antene i okruzenja</p>	kom	1.95