

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

ACC. KONTROLERI - NAJVIŠI STEPEN SIGURNOSTI - PROFI OPREMA







	1 1 ACC. Kontroler za JEDNA vrata za DVE wiegand (26, 34, 37) periferije (RFID čitača,...) - TCP/IP Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za jedan Exit taster, za jedan senzor vrata; za jedan PP alarm - IZLAZI (relay): za jedna vrata; za jednu sirenu	kom	145.00
	1 2 ACC. Kontroler za DVOJA vrata za ČETIRI wiegand (26, 34, 37) periferije (RFID čitača,...) - TCP/IP Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za dva Exit tastera, za dva senzora vrata; za dva PP alarma - IZLAZI (relay): za dvoja vrata; za dve sirene	kom	195.00
	1 4 ACC. Kontroler za ČETVORA vrata za ČETIRI wiegand (26, 34, 37) periferije (RFID čitača,...) - TCP/IP Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za četiri Exit tastera, za četiri senzora vrata; za dva PP alarma - IZLAZI (relay): za četvora vrata; za dve sirene	kom	225.00
	1 5 ACC. Kontroler za ČETVORA vrata OSAM x wiegand (26, 34, 37) periferija (RFID čitača,...) - RS485 za OSAM periferija (RFID čitača, bar code skenera, itd) - TCP/IP Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera - ULAZI: za četiri Exit tastera, za četiri senzora vrata; za dva PP alarma	kom	275.00
	1 6 LINUX ACC. Kontroler za ČETVORA VRATA OSAM PERIFERIJA (RFID ČITAČA, ILI ...) - PRERIFERIJE MAX. OSAM wiegand (26, 34, 37) PERIFERIJA (RFID čitača,...), ILI - PRERIFERIJE MAX. OSAM RS485 PERIFERIJA (RFID čitača, bar code skenera, itd) - TCP/IP Kapacitet: ID 30,000; Rec. 60,000; anti-pass; on-line ili off line režim rada - Web Server (SDK) do max. 254 kontrolera	kom	295.00
	1 7 Acc. Kontroler Lift, Pretinci, ... 32 x Relay: 2xWiegand Citac; 32 x senzor vrata; 1 x PP alarm - Izlazi (relay): 32 x vrata; 2 x (PP Sirena&Svetlo) bez kutije i napajanja - TCP/IP - Web Server, opcija RS485 (do max. 254 Acc. Kontroler) - ID 120,000; Rec. 200,000	kom	345.00

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

RFID ČITAČI KARTICA - WIEGAND PLATFORMA & SAMOSTALNI

	2 37 AEM1000-125KHz	kom	30.00
	RFID Čitač Kartica EM (125KHz) wiegand reading distance : 30 ~ 120mm - Max. rastojanje od Acc. Kontrolera < 150m -25°C ~ 70°C - Unutrasnja (spoljna natkrivena) primena LED (blue - green - LOGO can be customerized		
	2 38 AEM1000-13.56MHz	kom	35.00
	RFID Čitač Kartica M1 (13.56MHz) wiegand reading distance : 30 ~ 120mm - Max. rastojanje od Acc. Kontrolera < 150m -25°C ~ 70°C - Unutrasnja (spoljna natkrivena) primena LED (blue - green - Logo: "ASPEKT" (po zahtevi možemo dodati i logo kupca, za kol. +50kom)		
	2 39 AHID-1000	kom	70.00
	RFID Čitač Kartica HID wiegand Reading HID card reading distance : 10--15CM - LED status: after powering, blue, and swipe card, change to Green - LOGO can be customerized		
	2 40 RA-128	kom	55.00
	RFID Citac Kartica EM, ili M1 Wiegand 26, 34 rang: 3 ~ 12cm - rastojanje od Acc. < 150m -20°C ~ 55°C Spoljna primena buzzer - Metalno kuciste, vodo-otporno DC12V ~ 15V, bez napajanja		
	2 41 ADT5515	kom	65.00
	RFID Citac Kartica EM: 125KHz, opcije M1 13.56MHz, HID, NFC rang: 3 ~ 7cm - Wiegand 26/34, rastojanje od Acc. < 100m Opcija RS485/RS232, od Acc. < 1200m - IP65, -45°C ~ 70°C metal case; water proof; Shockproof; anti vandal - Namenjen za izrazito teške uslove rada		
	2 45 ACAM211B-EM	kom	55.00
	Seriya GB RFID Citac Kartica EM 125KHz Wiegand & STAND ALONE + ulaz za eksterni citac - Šifrator "touch metal keypad" rang: 3 ~ 12cm rastojanje od Acc. < 150m - Spoljna primena buzzer metalno kuciste, vodo-otporno - DC12V ~ 15V; ID Card, Users 2000 -20°C ~ 55°C		
	2 46 AMA-1	kom	75.00
	RFID Citac Kartica EM, ili Mifare Wiegand & STAND ALONE + ulaz za eksterni citac - Šifrator "touch keypad" rang: 3 ~ 12cm rastojanje od Acc. < 150m -20°C ~ 55°C - Spoljna primena (natkriveno) buzzer metalno kuciste, vodo-otporno - DC12V ~ 15V; ID Card, Users 2000		

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	2 48 U2 RFID Citac Kartica EM, ili Mifare Wiegand 26/34 input & output & STAND ALONE - METALNO KUČIŠTE; vodo-otporno IP68; anti vandal LED, buzzer - Rang: 3 ~ 12cm rastojanje od Acc. < 150m -35°C ~ 60°C - DC12V; ID Card, Users 2000 Certification: RoHs, FCC, CE	kom	75.00
	2 50 DT5522ID RFID Citac Kartica EM, ili M1 Tastatura & LCD Displej RS485 rang: 3 ~ 12cm - Rastojanje < 1,200m -20°C ~ 55°C Unutrasnja primena buzzer DC12V ~ 15V !	kom	125.00
	2 52 AF6-USB Fingerprint Scanner RFID (EM) REader out door metal case; water proof; anti vandal - USB; RS232; RS485; wiegand 26, 34 stand alone Fingers 1000 ID Card 1000 - 2xFinger; 1xCard Card, ili FP Card + FP	kom	135.00
	2 55 AS600-EM Citac Kartica EM (125MHz) Wiegand & STAND ALONE Šifратор "metal keypad" IP68 - rang: 3 ~ 12cm rastojanje od Acc. < 150m -45°C ~ 60°C Spoljna primena; buzzer - metalno kućiste, vodo-otporno; anti-vandal DC12V ~ 15V - U "stand alone" režimu kapacitet 2,000 (RFID Kartica, PWD različitih) - Na "wiegand"-u kapacitet 30,000 (RFID Kartica, PWD različitih)	kom	70.00
	2 56 AS600-MIFARE Citac Kartica MIFARE Wiegand & STAND ALONE Šifратор "metal keypad" IP68 - rang: 3 ~ 12cm rastojanje od Acc. < 150m -45°C ~ 60°C Spoljna primena; buzzer - metalno kućiste, vodo-otporno; anti-vandal DC12V ~ 15V - U "stand alone" režimu kapacitet 2,000 (RFID Kartica, PWD različitih) - Na "wiegand"-u kapacitet 30,000 (RFID Kartica, PWD različitih)	kom	70.00
	2 57 AHCC760-MSR Citac Kartica Mag. Stripe Wiegand26 "swipe" - kontakt - Rastojanje od Acc. < 100m -10°C ~ 70°C Metalno kuciste	kom	125.00

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

RFID ČITAČI KARTICA - WiFi; TCP/IP; WIEGAND

4 88

YAFBAK-8100

kom

95.00

- SAMOSTALNI RFID ČITAČ-RFID MIFARE-"TOUCH" TASTATURA | IP66 | SERIJA 4000
- Opcije otključavanja: autorizovana ŠIFRA i/ili RFID Kartica i/ili korisnički mobilni telefon
 - Upravljanje sistemom: "master" mobilni telefon (ANDROID, IOS, Bluetooth 4.0)
 - Kapacitete: 20.000 RFID Kartica | ŠIFRA i/ili Korisničkih mob. Telefona: ne ograničen



4 89

YAFBA-8100

kom

90.00

- SAMOSTALNI RFID ČITAČ-RFID MIFARE-ZVONCE "TOUCH" TASTER | IP66 | SERIJA 4000
- Opcije otključavanja: autorizovana RFID Kartica i/ili korisnički mobilni telefon
 - Upravljanje sistemom: "master" mobilni telefon (ANDROID, IOS, Bluetooth 4.0)
 - Kapacitete: 20.000 RFID Kartica | Korisničkih mob. Telefona: ne ograničen
 - Napajanje 12VDC; potrošnja 50mA; materijal: tamperisano staklo, aluminijumski okvir

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

RFID (UHF) ČITAČI KARTICA - DUGOG DOMETA - WIEGAND PLATFORMA

5 91

AZT | UHF Čitač | sa MINI antenom, rang >3m | RS232, RS485, wiegand 26/34 |
- 170 × 120 × 50 mm | 902~928MHz, 865~868MHz | -25°C~+95°C; 1.0kg | DC 7.5V~12V, 3A
- Support protocols: ISO18000-6B, EPC Class 1, EPC Class 1 GEN 2 | SDK
- RF power range: 0~30 dBm | Identify tag mode: trigger, or auto
- Frekvencije dozvoljene za javnu upotrebu u Evropi 868MHz



5 92

UHF Citac dugog dometa | 1 ~ 6m | RS232, RS485, wiegand 26/34 | EU slobodna za koriscenje frekvencija; protocol:
ISO-18000-6B/6C | DLL | ugaona polarizacija |



5 93

UHF Citac dugog dometa | > 15m | RS232, RS485, wiegand 26/34 | EU slobodna za koriscenje frekvencija; protocol:
ISO-18000-6B/6C | DLL | Ugaona polarizacija |

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

DATA TERMINALI - RFID & TASTATURA



7	102	ASC103/ASC403	kom	185.00
---	-----	---------------	-----	--------

DATA TERMINAL | RFID (125KHz) TA+ACC | EVIDENCIJA I KONTROLA PRISTUPA
 - TCP/IP, USB host, RS232/485; 30,000 user; 50,000 records; anti-pass back; webserver
 - 50 x Time Zone, 5 x Grouping, 10 x Combination | Wiegand In/Out
 - Audio Visual Indicator: Red LED (Access denied) / Green LED (Access granted)
 - With Audible Beep; Dim: 159*136*40mm; 0°C ~ 45°C; RH 20% ~ 80%



7	103	ACAM103	kom	195.00
---	-----	---------	-----	--------

DATA TERMINAL | RFID (13.56GHz) TA+ACC | EVIDENCIJA I KONTROLA PRISTUPA
 - TCP/IP, USB host, RS232/485; 30,000 user; 50,000 records; anti-pass back; webserver
 - 50 x Time Zone, 5 x Grouping, 10 x Combination | Wiegand In/Out
 - Audio Visual Indicator: Red LED (Access denied) / Green LED (Access granted)
 - With Audible Beep; Dim: 159*136*40mm; 0°C ~ 45°C; RH 20% ~ 80%



7	108	AE01-NET-B-K	kom	95.00
---	-----	--------------	-----	-------

DATA TERMINAL | AOP | RFID Čitač Kartica & TASTATURA & ZVONCE | ETHERNET (TCP/IP)
 - ID Card holder: 21000, Logs | 50,000 Alarm; 60,000 Events
 - External Card reader (1) IN on wiegand; EXIT button (1) IN; Fire alarm (1) IN
 - Door sensor (1) IN; Door lock NO/NC (1) OUT; Zvonce (1) NC OUT



7	109	AE01-NET-B-LCD	kom	100.00
---	-----	----------------	-----	--------

DATA TERMINAL | AOP | RFID Čitač Kartica & TASTATURA & ZVONCE | LCD | ETHERNET (TCP/IP)
 - ID Card holder: 21000, Logs | 50,000 Alarm; 60,000 Events
 - External Card reader (1) IN on wiegand; EXIT button (1) IN; Fire alarm (1) IN
 - Door sensor (1) IN; Door lock NO/NC (1) OUT; Zvonce (1) NC OUT

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

RFID (UHF) ČITAČI KARTICA - DESK TOP







	8 111 ADT5512- USB Citac Kartica RFID EM: 125KHz USB rang: 3 ~ 15cm	kom	33.00
	8 112 ADT5512-USB -MF Citac Kartica RFID Mifare: 13.56KHz USB rang: 3 ~ 15cm	kom	39.00
	8 113 ADT5512-HID-R HID USB READER Interface: USB Read HID 26,34,35,36,37,40bits (125khz)	kom	125.00
	8 116 ADT5512-HID HID PROGRAMER Interface: USB Providing many interface functions Program - HID 26,34,35,36,37,40bits compatible cards	kom	750.00
	8 117 AER300L NFC card issuer, send NFC UID card no. we can set card output no. format, - working with NFC mobile phone.	kom	95.00
	8 118 AER302 NFC card writer, can change Ultralight card to NFC card, provide SDK, and samples, - can identify different types of card, read and write NFC tags, - Elink make website linking automatically, - Eflow makes text input, Epurse can realize consumption, - and can save consumption records.also write person and things info.	kom	125.00
	8 119 AZT-STU-6212 AZT UHF RFID Desktop Reader/writer USB effective distance up to 100cm - 120×78×25 mm 902~928MHz, 865~868MHz -20°C~+65°C - Tag protocols: ISO18000-6B,EPC Class 1,EPC Class 1 GEN 2; Software Development Kit - Communication interface: Double USB (1.USB to serial port, 2.USB to keyboard input)	kom	225.00

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
------	----------------	----	------------

KONVERTER I DETEKTORI ZA INDUKTIVNE PETLJE

	9 122 RS232-WG KONVERTER RS232 na Wiegand 26, 34	kom	45.00
	9 131 APS26 KONVERTER PS2 na Wiegand 26, 34 - PS2 to Wiegand 26bit or Wiegand 34bit	kom	70.00
	9 132 AWST-RS2322WG KONVERTER RS232 na Wiegand 26, 34 - converter support double-way transmission; Wiegand 26bit or Wiegand 34bit to RS232 - RS232 to Wiegand 26bit or Wiegand 34bit	kom	45.00
	9 133 AWST-WG2USB KONVERTER USB na Wiegand 26, 34 - converter support double-way transmission; Wiegand 26bit or Wiegand 34bit to USB - USB to Wiegand 26bit or Wiegand 34bit	kom	75.00
	9 141 PD-132 Kontroler za induktivnu petlju AOP (DIN šina); 1Ch; 4 nivoa osetljivosti 230V / 5A - 4 frekventna opsega 3 rezima rada 2 relejna izlaza -20 ~ 65°C - Opcija: 24VDC CE, FCC i RoHS Sertifikati	kom	85.00
	9 142 PD-234 Kontroler za induktivnu petlju AOP (DIN šina); 2Ch; 4 nivoa osetljivosti 230V / 5A - 4 frekventna opsega 3 rezima rada 4 relejna izlaza -20 ~ 65°C - Opcija: 24VDC CE, FCC i RoHS Sertifikati	kom	125.00