

FOTO	OPIS PROIZVODA	STANJE	CENA (EUR)
------	----------------	--------	------------

1 ALTERNATIVE INDUKTIVNIM PETLJAMA



1	1	IDAL-VBR10B	6	115.00
---	---	-------------	---	--------

ALTERNATIVA ZA INDUKTIVNU PETLJU | IDAL-VBR10B | Radar Detector
 - Nije potrebno prosecanje asfalta, pogodan za sve vrste saobraćajnica
 - Rang detekcije 1 ~ 6m; za vozila; podesivo ± 0.1m | Za osobe do 1.5m
 - Horizontalni snop 30° ; vertikalni snop 17°
 - Radna temperatura od -40°C do + 85°C; Stepen zaštite IP67
 - 12VDC; 150mA; Isporučuje se bez napajanja
 - Preporučeno pozicioniranje na visinu 600mm od osnove saobraćajnice



1	2	IDAL-VBR10	0	125.00
---	---	------------	---	--------

ALTERNATIVA ZA INDUKTIVNU PETLJU | IDAL-VBR10 | Radar Detector
 - Nije potrebno prosecanje asfalta, pogodan za sve vrste saobraćajnica
 - Rang detekcije 1 ~ 6m; za vozila; podesivo ± 0.1m | Za osobe do 1.5m
 - Ne detektuje, eventualno postavljenu "krutu zavesicu" ispod letve rampe
 - Horizontalni snop 30° ; vertikalni snop 17°
 - Radna temperatura od -40°C do + 85°C; Stepen zaštite IP67
 - 12VDC; 150mA; Isporučuje se bez napajanja
 - Preporučeno pozicioniranje na visinu 600mm od osnove saobraćajnice



1	3	IWAD-400-2	2	145.00
---	---	------------	---	--------

ALTERNATIVA ZA INDUKTIVNU PETLJU | IWAD-400-2 | Elektro magnetni Detector
 - Nije potrebno prosecanje asfalta, pogodan za sve vrste saobraćajnica
 - Rang detekcije ≥ 1.5 ~ 2m; Horizontalni snop 35° ± 5°; vertikalni snop 15° ± 3°
 - Radna temperatura od -40°C do + 85°C; Stepen zaštite IP67
 - 12VDC; 250mA; Isporučuje se bez napajanja
 - Preporučeno pozicioniranje na visinu 600mm ~ 800mm od osnove saobraćajnice



1	4	FAJC-DL001	0	245.00
---	---	------------	---	--------


ALTERNATIVA ZA INDUKTIVNU PETLJU | FAJC-DL001 | Radar Detector | 12VDC
 - Nije potrebno prosecanje asfalta, pogodan za sve vrste saobraćajnica
 - Detektuje i vozila i ljude i ISTOVREMENO RAZLIKUJE vozila, odnosno ljude
 - Rang detekcije 0.1m ~ 3.9m; Korak: 0.1m; Snop ide po visini: 54°; po širini: 28°
 - 12VDC; 150mA; Isporučuje se bez napajanja
 - Preporučeno pozicioniranje na visinu 600mm~760mm od osnove saobraćajnice



1	5	FAJC-DL002	0	195.00
---	---	------------	---	--------

DALJINAC ("DE-BUGGER") - Služi za kontrolu i podešavanje FAJC-DL001

2 MIKRO-TALASNI DETEKTOR KRETANJA VOZILA I LJUDI

FOTO	OPIS PROIZVODA	STANJE	CENA (EUR)
	2 1 IDAL-VMD10-B MIKRO-TALASNI SENZOR KRETANJA DETEKUJE LJUDE I VOZILA BLACK - Microwave Motion Sensor for Automatic Door Opener MIN. 5cm/sec - Working Principle: Doppler effect; Center Frequency: 24.125GHz - Maximum Installation Height: Less than 5m; Relay Output: COM NO - Hold Time: 0.5 seconds; Wire Length: 2.5m; Temperature Range: -25°C to +85°C - Housing Material: ABS plastic; Housing Color: black, silver gray - Power Supply Voltage: 12-24V; Dimensions: 120 (L)*80 (W)*52mm (H)	0	45.00
	2 2 IDAL-VMD10-S MIKRO-TALASNI SENZOR KRETANJA DETEKUJE LJUDE I VOZILA SILVER - Microwave Motion Sensor for Automatic Door Opener MIN. 5cm/sec - Working Principle: Doppler effect; Center Frequency: 24.125GHz - Maximum Installation Height: Less than 5m; Relay Output: COM NO - Hold Time: 0.5 seconds; Wire Length: 2.5m; Temperature Range: -25°C to +85°C - Housing Material: ABS plastic; Housing Color: black, silver gray - Power Supply Voltage: 12-24V; Dimensions: 120 (L)*80 (W)*52mm (H)	7	45.00
	2 3 MA-204 MIKRO-TALASNI SENZOR KRETANJA DETEKUJE LJUDE I VOZILA "ZAVESA" - Microwave Motion Sensor for Automatic Door Opener MIN. 5cm/sec - Working Principle: Doppler effect; Center Frequency: 24.125GHz - Maximum Installation Height: Less than 5m; Relay Output: COM NO - Hold Time: 0.5 seconds; Wire Length: 2.5m; Temperature Range: -25°C to +85°C - Housing Material: ABS plastic; Housing Color: black, silver gray - Power Supply Voltage: 12-24V; Dimensions: 120 (L)*80 (W)*52mm (H)	0	45.00
	2 4 IDAL-VMD20 DETEKTOR (SMER) KRETANJA VOZILA IDAL-VMD20 DETEKUJE SAMO VOZILA - Working Temperature: -40°C to +80°C; Housing Material: ABS - IDEALAN ZA AUTOMATSKA ROLO VRATA NA MAGACINIMA, I INDUSTRIJI ITD. - Power Supply: 12-24VDC; Center Frequency: 24.125GHz; Installation Height: 2.5-5m - Detection Mode: One-way detection / Two-way - Holding Time: 1s; Relay Output: COM NO NC - VIDEO: https://www.youtube.com/watch?v=P8Wscu_3pqc	1	175.00