



A6000-DMF1 RFID Kartica (MF1)

Applicable card	TEMIC contact less RF card or MIFARE ONE contact less RF card.
Power supply	4pcs standard AA alkaline batteries.
Battery life	About 10 months in normal state, depending on usage and climatic conditions.
Low voltage warning	When power's voltage is less 4.5V, there will be warning when unlock. The lock still can be unlocked about 100 times before the batteries are replaced.
Static consumption	12uA
Dynamic consumption	200mA
Open time	The lock will be locked again automatically 7 seconds after unlocking.
Reliability of card operation	No accident for 1000 times of continuous card operation.
Emergency unlocking	The door can be unlocked by Master Card or Mechanical key even though the deadbolt works.
Installation request	To be installed on the door, with the door thickness between 33mm to 50mm, and if the door surface is decorated, the distance between the decoration edge to the door edge must be over 86mm.
Panel size	168mm(Height) ×70mm (Width) ×59mm (Thickness)
Mortise size	Standard single latch 60mm
Weight	2.5Kg
Material	Alloy
Handle orientation	Left hand push to open, right hand push to open; left hand pull to open, right hand pull to open.



Material	Flank plate	Stainless steel 304
	Latch & Bolt	Stainless steel 304
	Cover	Stainless steel 201

Single latch

CE FC RoHS COMPLIANT ISO 9001(2008)