



700.00€



LPR (ANPR) IP KAMERA

Model: ITC237-PW6M-(IR)LZF1050-B

- 2MP Long Range Access ANPR Camera
- CMOS image sensor
- Video compression standards: H.265/H.264M/H.264H/H.264B/MJPEG
- Integrated design, IP67



Image Processing

Illuminator	6 IR illuminators (brightness adjustable)
Image Sensor	1/1.8" CMOS
Image Resolution	1920 × 1080 (OSD black strip excluded)
Video Resolution	Main stream: 1080P (1920 × 1080) / 720P (1280 × 720) Sub stream: 720P (1280 × 720) / D1 (704 × 576, 704 × 480) / CIF (352 × 288, 352 × 240)
Video Frame Rate	PAL: Main stream (1920 × 1080@25fps, 1280 × 720@25fps), sub stream: (1280 × 720@25fps, 704 × 576@25fps, 352 × 288@25fps) NTSC: Main stream (1920 × 1080@30fps, 1280 × 720@30fps), sub stream (1280 × 720@30fps, 704 × 408@30fps, 352 × 240@30fps)
Bit Rate	H.264B: 32Kbps–32768Kbps H.264M: 32Kbps–32768Kbps H.264H: 32Kbps–32768Kbps H.265: 32Kbps–32768Kbps MJPEG: 512Kbps–65536Kbps
Video Encoding	H.264B/H.264M/H.264H/H.265/MJPEG
Image Encoding	JPEG
Noise Reduction	3DNR
White Balance	Full auto; auto color temperature range; customized color temperature
Electronic Shutter	1/50–1/10000, auto or manual
Wide Dynamic Range	96db
+ Edge Enhancement	Yes
+ Exposure Mode	Full auto; customized auto; customized

Iris	Auto iris (W:1.3–T:2.3)
Function	
Trigger Mode	Video detection; I/O coil; video detection and I/O coil
Shutter	Single shutter
Storage	1 built-in TF card port. Kingston 16G, 32G and 64G; Dahua 16G, 32G and 64G; SanDisk 16G, 32G and 64G
Image Tampering Prevention	Yes. Video/picture can be checked through watermark and verification
Max Illumination Distance	30 m (98.43 ft)
Capture Range	8 m–30 m (26.25 ft–98.43 ft)
Detected Lane Width	6 m –7 m (19.69 ft–22.97 ft)
Min Ambient IL luminance	0.002 Lux. Illuminator is designed with the camera for illumination
Max Speed that the Camera Detects	60 km/h
Alarm Event	Alarm in the case of no storage card, not enough storage space, storage card error, network disconnection, IP conflict, and illegal access
Security Mode	Authorized username and password, MAC address binding, HTTPS encryption, IEEE 802.1x, and network access control
OSD Overlay	Supports overlay of time, address (position of channel), lane (number/direction), plate (number and color), vehicle (speed, color, type)
ANR (Automatic Network Replenishment)	Yes. Platform/FTP
Auto Register	Yes
Intelligence	
Vehicle Detection	Vehicle capture rate $\geq 99\%$
Vehicle Recognition	Supports recognizing vehicle type, vehicle logo, vehicle color, license plate, and vehicle without plate. Vehicle recognition rate $\geq 95\%$
Video Metadata	Yes
Intelligent Track Frame	Intelligent frame display. Supports displaying vehicle plate and vehicle path
Ports	
Lens	Lens in the camera module
Analog Output	1
Ethernet Port	1 100/1000M Ethernet port (RJ45)
RS-485 Port	2
RS-232 port	1
Alarm Input	3, optocoupler input (switch quantity)
Alarm Output	3 ports. 2-channel optocoupler output, 1-channel relay output, which can connect to devices such as barriers
Audio Input	1-channel RCA port
Audio Output	1-channel RCA port
General	
Power Supply	12V DC, 24V AC, PoE+
Power Consumption	< 20W
+ Working Temperature	-30°C to +65°C (-22°F to +149 °F)
+ Working Humidity	10%–90% (no condensation)

Housing	Metal and plastic
Protection Grade	IP67
Dimensions (L×W×H)	515.2mm×124.7mm×183.2mm (20.28"×4.91"×7.21")
Net Weight	1.9kg (4.19lb)
Gross Weight	3.3kg (7.28lb)
Installation	Universal joint installation
Lens	10mm–50mm (0.39"–1.97")
Certification	
CE, FCC	Yes
RoHS	Yes



+381 11 355 7599
+381 63 598 017
office@aspekt.rs