

SAMOSTALAN ACC. KONTROLER

PART No: Sboard-BT

NA KOJI SE MOŽE POVEZATI BILO KOJA „WIEGAND“ PERIFERIJA
ODNOSNO, RFID ČITAČ, SKENER OTISKA PRSTA, BARCODE SKENER ITD.
APP download is available for Android only; APP name: Ksmart

NIŽE, U ORIGINALU

Sboard-BT
Bluetooth Access Controller
Compatible with all Bluetooth-enabled mobile phones
(version: 4.0 above) to access the door
APP support Android 4.3 and IOS7.0 above
1,000 users, user data can be transferred
Multi access modes: Card, Card or PIN, Card with PIN
and multi Cards/PINs
Can connect with any reader with Wiegand 26~37 bits
output
Can connect with any keypad reader with 4bits, 8bits
(ASCII), or 10bits Virtual number output

Sboard-BT (BLUE TOOTH)
MINI ACC. Kontroler+Daljinac & BT
1xVrata; 1xRFID; 1xEXIT; WG In/Out
“Stand alone” za 1000 Korisnika



Model	Sboard-BT
Product Name	Bluetooth Access Controller
User Capacity	1000
Operating Voltage	9~24V DC
Idle Current	< 20mA
Relay	One (NO, NC, Common)
Adjustable Relay Output Time	0~99 Seconds (5 seconds default)
Lock Output Load	2 Amp Maximum
Wiegand Input	Wiegand 26~37 bits
Wiegand Output	Wiegand 26~37 bits (for user transfer)
Environment	Indoor
Operating Humidity	0 ~ 90%RH
Physical	ABS Shell
Colour	Black
Dimensions	6.5L x 5.4W x 1.9H (cm)
Unit Weight	0.1KG
Standard Package	82PCS/carton
Carton Weight	8.2KG
Carton Size	34*40*33.5 (cm)



+381 11 355 7599
+381 63 598 017
office@aspekt.rs