

SAMOSTALAN KONTROLER

PART No: Sboard

NA KOJI SE MOŽE POVEZATI BILO KOJA „WIEGAND“ PERIFERIJ
ODNOSNO, RFID ČITAČ, SKENER OTISKA PRSTA, BARCODE SKENER ITD.



NIŽE, U ORIGINALU

Mini Single Door Controller

1,000 users, user data can be transferred

Multi-access modes: Card, Card or PIN, Card with PIN and multi Cards/PINs

Can connect with any reader with Wiegand 26~37 bits output

Can connect with any keypad reader with 4bits, 8bits (ASCII), or 10bits Virtual number output

User Capacity	1,000
Operating Voltage	9~24V DC
Idle Current	< 20mA
Relay	One (NO, NC, Common)
Adjustable Relay Output Time	0~99 Seconds (5 seconds default)
Lock Output Load	2 Amp Maximum
Wiegand Interface	
Input	Wiegand 26~37 bits
Output	Wiegand 26~37 bits (for user transfer)
Environment	Indoor
Operating Humidity	0 ~ 90%RH
Physical	ABS Shell
Colour	Black
Dimensions	65L x 54W x 19H (mm)
Unit Weight	40g
Shipping Weight	100g



+381 11 355 7599
+381 63 598 017
office@aspekt.rs