








MERNE SONDE:

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	<p>41 RKA100-02 CE</p> <p>RKA Wind Speed Anemometer Sensor Carbon Fiber - Pulse, 4-20mA, RS485, 0-5V Material: Carbon Fiber; Power Supply: 12-24VDC - Accuracy: ±3%FS; Ingress Protection: IP65; Operating Temperature: -40°C+50°C; - Limit Wind Speed: 50m/s; CE Certified</p>	kom	95.00
	<p>42 RKA100-01 CE</p> <p>RKA Wind Speed Anemometer Sensor Metal - Pulse, 4-20mA, 0-5V Material: Metal; Power Supply: 12-24VDC - Accuracy: ±3%FS; Ingress Protection: IP65; Operating Temperature: -30°C +70°C; - Limit Wind Speed: 70m/s; CE Certified</p>	kom	110.00
	<p>43 RKA120-01C</p> <p>RKA Wind Speed and Direction Sensor CE Certified Material: Aluminum alloy and carbon fiber Wind speed range: 0-45m/s(current or voltage output); 0-70m/s(pulse,RS485,RS232 output) Wind speed resolution: 0.1m/s; Wind speed accuracy: ±(0.3+0.03V)m/s ,V is current wind speed Wind direction range: 0-360°; Wind direction resolution: 1°; Wind direction accuracy: ≤ ±3° Output: RS485, 4-20mA, 0-5V, RS232, pulse (NPN, only for wind speed)</p>	kom	295.00
	<p>45 RAK400-02</p> <p>RKA Rain & Snow Sensor NO Theory: Inductance Sensor - Output: Switching Transducer; Description: Rain Snow Sensor; Item: Rain Snow Sensor - Coil material: Gold-plated(Strong corrosion resistance), Shell material: ABS - Supply voltage: 12~24VDC; Load Capacity(relay): AC120V/2A ,DC24V/2A - Automatic heating: Heating power: 10W max - Diemeion: 90*60*40mm; IP Grade: IP67; Certificate: CE</p>	kom	85.00
	<p>46 RKA400-04</p> <p>RKA Rain Gauge Sensor CE Certified</p>	kom	195.00

MERNE SONDE:

FOTO	OPIS PROIZVODA	JM	CENA (EUR)
	47 RKA310-01 RKA Ambient Temperature Sensor PT100/PT1000 - Output: PT100/PT1000; Accuracy: PT100/PT1000 class A; Probe material: 304SS - Probe dimension: dia: 6mm, length: 50mm; Cable length: 1.5m standard; IP grade: IP67 - Solar radiation shield: Yes, RK95-01 optional; Certificate: CE ROHS	kom	35.00
	48 RKA510-01 RKA Soil Moisture Sensor - Range: 0-100%(m3/m3); Output Signal: 4-20mA ,0-5V,0-2V, RS485 optional - Response Time: <1s; Power: 5VDC, 12-24VDC; Probe material: 316L stainless steel - Housing material: ABS; Accuracy: ±2%; IP Grade: IP68	kom	145.00
	51 THP21SN-d THP21SN-d/Temperetura&Vlaznost/Transmitter	kom	95.00