

IP KAMERA: VART-C18 Tuya

IDEALNA PODRŠKA KOMPLEKSNUM INTERFONSKIM (AUDIO) SISTEMIMA

Recimo za velike rezidencijalne objekte, vile, apartmanske sisteme itd.

Ili umesto interfona, ima dvosmeru audio komunikaciju (mikrofon, zvučnik) sa mob. Telefonom.

Detektuje osobu u zadatom „frame“ i automatski signalizira isto na mob. telefon.



Model:	VART-C18 Tuya
APP:	Tuya Smartlife
System structure:	Embedded Linux system, ARM chip structure
Chip:	AK330
Resolution:	2.0MP
Sensor Resolution:	1/2.9"SC2335H 1920x1080
Lens:	4MM
View angle:	85°
Pan-tilt:	Rotates Horizontal:355° Vertical: 90°
Preset point quantity:	6
Video compression standard:	H.265/20FPS
Video format:	PAL
Minimum illumination:	0.01Lux@ (F2.0, VGC ON),0.Luxwith IR
Electronic shutter:	Auto
Backlight compensation:	Support
Noise reduction:	2D、3D
LED quantity:	8pcs white LED + 8pcs Infrared LED
Network connection:	WIFI, AP Hotspot, RJ45 Network port
Network:	WIFI wireless transmission (support IEEE802.11b/g/n wireless protocol).
Night vision:	IR-CUT switch Automatic, about 5-8meters (It varies from environment) White Led can be remote control via APP:①Turn ON ②Turn OFF ③ Auto (In automatic mode, the infrared light will be turned ON after the IR-cut switch to night vision automatically, it can intelligently detected human body, and Turn ON/OFF the White light intelligently)
Audio:	Built-in microphone and speaker, support two-way audio and real-time transmission. ADPCM audio compression standard, self-adapt to code stream
Network protocol:	TCP/IP、 UDP、 HTTP、 DDNS、 DHCP、 FTP、 NTP
Alarm:	①Motion detection and picture push ②AI Human intrusion Detection (optional)
Storage:	TF Card (Max 128G) ; Cloud storage /Cloud disk (optional)
Power input:	12V/2A Waterproof power supply (not including power supply)
Work environment:	Working temperature:-10°C ~ + 50°C Working Humidity: ≤95%RH



+381 11 355 7599
+381 63 598 017
office@aspekt.rs